Synergy® Sleek Design

British standard socket outlets and USB sockets

8320 75

8322 61

8324 89

8320 44

8324 78

Sleek design
BSS : Plates made of austenitic Stainless Steel - non-magnetic - grade 304 L
PSS : Plates made of Stainless Steel + rust resistance
G : Plates made of Stainless Steel + rust resistance
Terminal screws captive and backed off ready for cabling - large angled terminal entries
Compact mechanism for maximum wiring space

Socket outlets 13 A - 250 V∿

Conform to BS EN 1363: Part. 2
With safety shutter mechanism
Flush mounting back box : min. 35 mm deep
ASTA licence

1 gang unswitched
Nominal plate dimensions : 86 x 86 mm

Pack	Cat. Nos.	
1	8320 65	Brushed stainless steel
1	8322 65	Polished stainless steel
1	8324 65	Gold

2 gang unswitched
Nominal plate dimensions : 86 x 146 mm

Pack	Cat. Nos.	
1	8320 75	Brushed stainless steel
1	8322 75	Polished stainless steel
1	8324 75	Gold

Double pole socket outlets 13 A - 250 V∿

Conform to BS EN 1363: Part. 2
With safety shutter mechanism
Flush mounting back box : min. 35 mm deep
ASTA licence

1 gang switched
Nominal plate dimensions : 86 x 86 mm

Pack	Cat. Nos.	
1	8320 60	Brushed stainless steel
1	8322 60	Polished stainless steel
1	8324 60	Gold

1 gang switched with blue LED power indicator
Nominal plate dimensions : 86 x 86 mm

Pack	Cat. Nos.	
1	8320 61	Brushed stainless steel
1	8322 61	Polished stainless steel
1	8324 61	Gold

2 gang switched
Nominal plate dimensions : 86 x 146 mm

Pack	Cat. Nos.	
1	8320 70	Brushed stainless steel
1	8322 70	Polished stainless steel
1	8324 70	Gold

2 gang switched with blue LED power indicators
Nominal plate dimensions : 86 x 146 mm

Pack	Cat. Nos.	
1	8320 71	Brushed stainless steel
1	8322 71	Polished stainless steel
1	8324 71	Gold

Socket outlets 15 A - 250 V∿

Conform to BS 546
Patented 3 pin safety shutter mechanism
Flush mounting back box : min. 35 mm deep
Nominal plate dimensions : 86 x 86 mm

1 gang switched

Pack	Cat. Nos.	
1	8320 89	Brushed stainless steel
1	8322 89	Polished stainless steel
1	8324 89	Gold

Socket outlets 5 A - 250 V∿

Conform to BS 546
Patented 3 pin safety shutter mechanism
Flush mounting back box : min. 25 mm deep
Nominal plate dimensions : 86 x 86 mm

1 gang switched - single pole

Pack	Cat. Nos.	
1	8320 69	Brushed stainless steel
1	8322 69	Polished stainless steel
1	8324 69	Gold

Socket outlets 2 A - 250 V∿

Conform to BS 546
Flush mounting back box : min. 25 mm deep
Nominal plate dimensions : 86 x 86 mm

1 gang unswitched

Pack	Cat. Nos.	
1	8320 59	Brushed stainless steel
1	8322 59	Polished stainless steel
1	8324 59	Gold

Double USB sockets

Conform to IEC 62684
Flush mounting back box : min. 40 mm deep
Input voltage : 110 V/ 230 V
5 V (output) - 2400 mA
Wiring with 1·5 mm² and 2·5 mm² (only live and neutral)
Nominal plate dimensions : 86 x 86 mm

Pack	Cat. Nos.	
1	8320 44	Brushed stainless steel
1	8322 44	Polished stainless steel
1	8324 44	Gold

Switched USB sockets

Conform to BS 1363-2
USB chargers conform to BS EN 60950-1

1 gang switched - single pole
USB Type-A 2·4 A - 5 V⎓ - 12 W
Consumption in passive mode < 0·08 W
Nominal plate dimensions : 86 x 86 mm

Pack		Cat. Nos.	
1	N	8320 78	Brushed stainless steel
1	N	8322 78	Polished stainless steel
1	N	8324 78	Gold

2 gang switched - single pole
USB Type-A + Type-C 3 A - 5 V⎓ - 15 W
Consumption in passive mode < 0·08 W
Nominal plate dimensions : 86 x 146 mm

Pack		Cat. Nos.	
1	N	8320 79	Brushed stainless steel
1	N	8322 79	Polished stainless steel
1	N	8324 79	Gold